U.S. Application No.: 09/851,247

Our Ref.: A7966 Art Unit: 2874

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1. (PREVIOUSLY PRESENTED) A fiber optic cable, comprising:

an outer layer;

at least one optical fiber disposed inside said outer layer;

at least one gel-swellable portion proximate to an inner surface of said outer layer; and

a water resistant gel positioned adjacent to said gel-swellable portion and disposed

between said outer layer and said optical fiber;

wherein said gel-swellable portion has a density of less than 0.90 g/cc and said outer layer has a density of at least 0.90 g/cc.

- 2. (PREVIOUSLY PRESENTED) The fiber optic cable according to claim 1, wherein said at least one gel-swellable portion is a continuous layer surrounding said at least one optical fiber.
- 3. (PREVIOUSLY PRESENTED) The fiber optic cable according to claim 1, wherein said at least one gel-swellable portion has an uneven thickness.
- 4. (PREVIOUSLY PRESENTED) The fiber optic cable according to claim 1, wherein said at least one gel-swellable portion has a smooth surface.

U.S. Application No.: 09/851,247

Our Ref.: A7966 Art Unit: 2874

5. (Previously Presented) The fiber optic cable according to claim 1, wherein said at

least one gel-swellable portion has at least one groove in a surface of said at least one gel-

swellable portion.

6. (Previously Presented) The fiber optic cable according to claim 1, wherein said at

least one gel-swellable portion is made from at least one longitudinally running strip.

7. (PREVIOUSLY PRESENTED) The fiber optic cable according to claim 1, further

comprising a second gel-swellable portion positioned between said gel-swellable portion and

said at least one optical fiber.

8. (Previously Presented) The fiber optic cable according to claim 1, wherein said at

least one gel-swellable portion has a corrugated surface which is adjacent to said gel.

9. (PREVIOUSLY PRESENTED) The fiber optic cable according to claim 1, wherein at least

one gel-swellable portion contacts said inner surface of said outer layer.

10. (PREVIOUSLY PRESENTED) The fiber optic cable according to claim 1, wherein

said at least one gel-swellable portion is one of a copolymer or terpolymer of polyethelene.

11. (PREVIOUSLY PRESENTED)

The fiber optic cable according to claim 1, wherein

said gel-swellable portion swells more than 10% at 85°C.

- 3 -

U.S. Application No.: 09/851,247

12. (ORIGINAL) The fiber optic cable according to claim 1, wherein said gel is a polyolefin oil based gel.

Our Ref.: A7966

Art Unit: 2874

13. (PREVIOUSLY PRESENTED) The fiber optic cable according to claim 1, wherein said at least one gel-swellable portion is a polyolefin swellable material.

14. (PREVIOUSLY PRESENTED) The fiber optic cable according to claim 1, wherein the material of said at least one gel-swellable portion is softer than the material of said outer layer.

15. (Previously Presented) A fiber optic cable, comprising:

an outer layer;

at least one optical fiber disposed inside said outer layer;

a gel-swellable portion contacting an outer surface of said optical fiber; and

a water resistant gel positioned adjacent to said gel-swellable portion;

wherein said gel swellable portion absorbs at least some of a said gel, and wherein said gel-swellable portion swells more than 10% at 85°C.

16. (PREVIOUSLY PRESENTED) The fiber optic cable according to claim 15, wherein said gel-swellable portion is a continuous layer surrounding said at least one optical fiber.

U.S. Application No.: 09/851,247

Our Ref.: A7966 Art Unit: 2874

17. (PREVIOUSLY PRESENTED) The fiber optic cable according to claim 15, wherein said gel-swellable portion has an uneven thickness.

18. (PREVIOUSLY PRESENTED) The fiber optic cable according to claim 15, wherein said gel-swellable portion has a smooth surface.

19. (PREVIOUSLY PRESENTED) The fiber optic cable according to claim 15, wherein said gel-swellable portion has at least one groove in a surface of said gel-swellable portion.

20. (PREVIOUSLY PRESENTED) The fiber optic cable according to claim 15, wherein said gel-swellable portion is made from at least one longitudinally running strip.

- 21. (PREVIOUSLY PRESENTED) The fiber optic cable according to claim 15, further comprising a second gel-swellable portion positioned between said gel-swellable portion and said outer jacket.
- 22. (PREVIOUSLY PRESENTED) The fiber optic cable according to claim 15, wherein said gel-swellable portion has a corrugated surface which is adjacent to said gel.
- 23. (ORIGINAL) The fiber optic cable according to claim 15, wherein said gelswellable layer has a density less than 0.90 g/cc.

Our Ref.: A7966 U.S. Application No.: 09/851,247 Art Unit: 2874

24. (ORIGINAL) The fiber optic cable according to claim 15, wherein said gelswellable layer is one of a copolymer or terpolymer of polyethelene.

25. (CANCELLED)

- The fiber optic cable according to claim 15, wherein said gel is a 26. (ORIGINAL) polyolefin oil based gel.
- 27. (Previously Presented) The fiber optic cable according to claim 15, wherein said gel-swellable portion is a polyolefin swellable material.
- 28. (Previously Presented) The fiber optic cable according to claim 15, wherein the material of said gel-swellable portion is softer than the material of said outer layer.
 - 29. (CURRENTLY AMENDED) A fiber optic cable, comprising:

an outer layer;

at least one optical fiber;

a water resistant gel disposed between said at least one optical fiber and said outer layer; and

at least one gel-swellable portion proximate to one of an inner surface of said outer layer and an outer surface of said optical fiber;

U.S. Application No.: 09/851,247

Our Ref.: A7966 Art Unit: 2874

wherein said gel-swellable portion is made from a material softer than said one of said inner surface and said outer surface to which said gel-swellable portion is adhered-proximate to.

- 30. (PREVIOUSLY PRESENTED) The fiber optic cable according to claim 29, wherein said at least one gel-swellable portion is a continuous layer.
- 31. (PREVIOUSLY PRESENTED) The fiber optic cable according to claim 29, wherein said at least one gel-swellable portion has an uneven thickness.
- 32. (PREVIOUSLY PRESENTED) The fiber optic cable according to claim 29, wherein said at least one gel-swellable portion has a smooth surface.
- 33. (PREVIOUSLY PRESENTED) The fiber optic cable according to claim 29, wherein said at least one gel-swellable portion has a groove in a surface of said at least one gel-swellable portion.
- 34. (PREVIOUSLY PRESENTED) The fiber optic cable according to claim 29, wherein said at least one gel-swellable portion is made from at least one longitudinally running strip.
- 35. (PREVIOUSLY PRESENTED) The fiber optic cable according to claim 29, further comprising a second gel-swellable portion positioned between said at least one gel-swellable portion and the other of said outer surface and said inner surface.

U.S. Application No.: 09/851,247

Our Ref.: A7966 Art Unit: 2874

36. (PREVIOUSLY PRESENTED) The fiber optic cable according to claim 29, wherein said at least one gel-swellable portion has a density less than 0.90 g/cc.

37. (PREVIOUSLY PRESENTED) The fiber optic cable according to claim 29, wherein said at least one gel-swellable portion is one of a copolymer or terpolymer of polyethelene.

38. (CANCELLED)

- 39. (ORIGINAL) The fiber optic cable according to claim 29, wherein said gel is a polyolefin oil based gel.
- 40. (PREVIOUSLY PRESENTED) The fiber optic cable according to claim 29, wherein said at least one gel-swellable portion is a polyolefin swellable material.
- 41. (PREVIOUSLY PRESENTED) The fiber optic cable according to claim 29, wherein said at least one gel-swellable portion has a corrugated surface.
- 42. (PREVIOUSLY PRESENTED) The fiber optic cable according to claim 15, wherein said optical fiber is part of an optical fiber ribbon.

U.S. Application No.: 09/851,247

Our Ref.: A7966 Art Unit: 2874

43. (PREVIOUSLY PRESENTED) The fiber optic cable according to claim 29, wherein said at least one gel-swellable portion swells more than 10% at 85°C.

44. (PREVIOUSLY PRESENTED) The fiber optic cable according to claim 29, wherein said at least one gel-swellable portion contacts said one of an inner surface of said outer layer and an outer surface of said optical fiber.